

Nanotech 400UPJG Specification Overview

System Configuration

Ultra-precision four axis jig grinding machining center	X, Y, Z, W
Slide type	Fully constrained oil hydrostatic box style
Slide drive (X,Y,Z)	Dual iron-less linear motors
Slide drive (W / reciprocation axis)	Precision ball screw
Feedback resolution	0.000001mm
Tool interface	HSK-E25

Capacity

Maximum workpiece dimension	400 mm x 400 mm (15.75 in. x 15.75 in.)
Maximum weight	250 kg (550 lbs.)
Table surface configuration	T-Slots -10-H2 & M8 Tapped Holes
X-axis travel (cross axis)	1000 mm (39.4 in.)
Y-axis travel (machine table)	400 mm (15.75 in.)
Z-axis travel	250 mm (9.8 in.)
W-axis travel (reciprocation axis)	90 mm (3.5 in.)
Distance from table surface to spindle gauge-line	150 – 400 mm (5.9 in. – 15.75 in.)

Speeds and Feeds

Vmax X & Y	6000 mm/min (236 in/min)
Vmax Z	4500 mm/min (177 in/min)
Vmax W	16000 mm/min (630 in/min)
Spindle speed	0 - 60,000 rpm

System Control

Control	Delta Tau 1GHz PowerPMAC
Data storage	500 GB hard drive
Interface	DVD RW Drive / 2X USB Ports / 10/100/1000 Ethernet Connection
Block look-ahead	20,000 blocks
Move segmentation time	250 μ s
Programming resolution	0.000001 mm
HMI	NanoSMART gesture based touch screen interface

Workpiece Accuracy

Hole roundness	$\leq 0.5 \mu\text{m}$
Positioning accuracy	$\leq \pm 0.5 \mu\text{m}$ over 100 mm

Note: All statements concerning accuracy are based on a calibration temperature of 20 +/- 0.5 degrees C (68 +/- 1.0 degrees F). In an effort to continually improve our product performance, specifications are subject to change without notice. (Please consult your sales representative for our latest specifications)

Moore Nanotechnology Systems, LLC
230 Old Homestead Hwy,
Swanzey, NH 03446 USA
Tel (603) 352-3030
Fax (603) 352-3363
Email: sales@nanotechsys.com
www.nanotechsys.com

Moore Tool Company, Inc.
800 Union Avenue
Bridgeport, CT 06607-0088 USA
Tel (203) 366-3224
Fax (203) 367-0418
Email: sales@mooretool.com
www.mooretool.com

